



Airtame 3 + Hybrid



Turn every **screen** into a communication tool

Airtame 3 makes it easy to **share your screen**, show relevant **signage** content, and run **video meetings** – without switching systems or plugging in cables. The Airtame device connects to any display via HDMI and supports a wide range of cameras, microphones, and speakers over USB.

Built for shared spaces, Airtame 3 works with the tools your team already uses: Microsoft Teams, Zoom, Google Meet, and Webex. You can join calls directly from your calendar, share your screen without joining the meeting, and **manage everything remotely** through Airtame Cloud.



Screen sharing



Video conferencing



Digital signage



Remote management




Emergency alerts

Software Specifications



Screen sharing

- Screen share from any device, Laptop, tablet, or phone
- Share browser tab, window, or whole screen
- Share directly from the browser without an app
- Native protocols (Miracast, AirPlay, Google Cast)
- Video and Audio sharing



Video conferencing

- Supports calls across Microsoft Teams, Google Meet, Zoom, and Webex
- Plug'n'play peripheral support
- Join upcoming meetings from a Google or Microsoft calendar
- Easily screen share from another device into a call
- Cast the call from a browser without an app



Digital signage

- Make playlists of 3rd party signage content
- Integrations to Google Slides, PowerPoint, Canva, Power BI, and many more
- Customize the home screen with meeting room status and instructions for sharing
- Schedule content to appear at certain times
- Support vertical aspect ratios



Remote management

- Access Airtame screens from anywhere in the world
- Schedule power management and automatic firmware updates
- Troubleshoot signage using live view of the screen
- Organize Airtame screens in groups
- Receive device alert when devices go offline



Emergency Alerts

- Interrupt screens sharing and video calls with emergency alerts
- Supported with APIs for easy integration to CAP and custom setups
- Already works with Raptor, CrisisGo, InformaCast, Omnilert, and more...
- Show custom "All clear" messages when the emergency is over
- Trigger using Airtame Cloud

Hardware Specifications

Model Number: AT-DG3-HYBRID-3Y

Ports

HDMI	2 x HDMI 2.0 (4K 60Hz)
USB-A	2 x USB-A 3.0
USB-C	1 x USB-C 3.1 Gen 2 (DP, PD, and Data) 1 x USB-C Power port
Ethernet	1 x Gigabit Ethernet with PoE+ support
Security	Kensington lock

Interface

Ethernet:	1 Gigabit
WiFi:	802.11ax, Tri-Band - 2.4 GHz / 5 GHz
Bluetooth:	5.3


Software

Operating System:	Airtame OS (Linux-based)
Device Management:	Airtame Cloud

Environment

Ambient Operating Temperature:	0 to 45 °C (32 to 113 °F)
Operating Altitude:	0 - 2000 MSL
Power Consumption at Idle	4.5-5W

What's in the box

Airtame 3 device	30W USB-C power adapter	Regional IEC C7 cable	5ft HDMI 2.0 Cable	6x adhesive strips	User Manual
					

Power Input

PoE IEEE 802.3at Type 2 PoE+ (RJ45 Connector)

42.5-57V == min 30W

USB-C PD - 20V

1.5A == 30W

Security

Web/Cloud Transport Encryption: TLS

Device APU Security: With password (SRP)

Streaming Encryption: AirPlay, Miracast, GoogleCast

Conferencing Encryption: TLS, WebRTC

Physical Security: Custom tamper-proofing, Kensington lock compatible

Device Dimensions

Width: 130.0 mm (5.12 in)

Depth: 85.0 mm (3.35 in)

Height: 36.5 mm (1.44 in)

Weight: 335 grams (12 ounces)

Box Dimensions

Width: 268.0 mm (10.55 in)

Depth: 169.0 mm (6.65 in)

Height: 95.0 mm (3.74 in)

Weight: 1210 grams (43 ounces)

Warranty

Hardware: 3 years